Spreader Settings - Single Pass

SETTINGS FOR SINGLE PASS APPLICATION = FULL RATE

Scotts Rotary Spreaders: AccuPro 2000 / SR 2000 / SR-1 / R8-A

					SPREA	READER SETTING AT FULL LABEL RATES													
PRODUCT NAME	ANALYSIS	TYPE OR	CONE	EFFECTIVE AMOUNT OF PRODUCT (g/m2) APPLIED AFTER ONE RUN:															
		TECHNOLOGY	SETTING	WIDTH (m)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	
Sierraform GT	all analyses	MU & SR-K	7	3.8		- 1	J	К	L	М	M½								
STEP	STEP Hi-Mag	Trace Elements	7	4.3	Н	1½	K½												
Greenmaster	all analyses	Pro-Lite	6	4.0			1	J	К	K½	L½								
Greenmaster Organic	all analyses	Organic																	
Sportsmaster	all analyses	Conventional	6	5.1			K	L	М	N	0	Р	Q	R	S	Т	U	V½	
Sportsmaster CRF	all analyses	Poly-S and/or Resin	4	5.2		L	M½	0	Р	Q½	S	T½							
Sportsmaster Organic	all analyses	Organic																	
Sierrablen Plus	all analyses	Poly-S and/or Resin	5	5.0			L	M½	N½	Р	Q	R	S½						
Sierrablen	all analyses	Poly-S and/or Resin	4	5.4			N	01/2	Q	R½	T½	>	Х	Q (x2)	R (x2)	R½ (x2)			
Fairwaymaster Mini	all analyses	Poly-S	5	5.0			L	M½	N½	Р	Q	R	S½				·		
H2PRO	H2PRO Granules	wetting agent	5	4.0		J	K½	М											

- Recommended spreader settings are given for a walking speed of approximately 5km/hour.
- Given spreader settings are recommendations only. Exact rates, using the settings given in this table, cannot be guaranteed as rates are dependent on the spreader itself and the accuracy of the person operating it.
- · Calibrate the spreader at regular intervals.



Spreader Settings - Double Pass

SETTINGS FOR DOUBLE PASS APPLICATION = HALF RATE

Scotts Rotary Spreaders: AccuPro 2000 / SR 2000 / SR-1 / R8-A

PRODUCT NAME	ANALYSIS	TYPE OR TECHNOLOGY			SPREADER SETTING AT HALF LABEL RATES													
				EFFECTIVE	AMOUNT OF PRODUCT (g/m2) APPLIED AFTER TWO RUNS:													
				WIDTH (m)	5	10	15	20	25	30	35	40	45	50	55	60	65	70
Sierraform GT	all analyses	MU & SR-K	7	3.8			H1⁄2	1	1½	J								
STEP	STEP Hi-Mag	Trace Elements	7	4.3	G½	н	1											
Greenmaster	all analyses	Pro-Lite	6	4.0					H1/2	- 1	1½							
Greenmaster Organic	all analyses	Organic																
Sportsmaster	all analyses	Conventional	6	5.1						К	K½	L	L½	М	M½	N	N½	0
Sportsmaster CRF	all analyses	Poly-S and/or Resin	4	5.2				L	М	M½	N½	0						
Sportsmaster Organic	all analyses	Organic																
Sierrablen Plus	all analyses	Poly-S and/or Resin	5	5.0				J½	К	L	L½	M½	N	N½				
Sierrablen	all analyses	Poly-S and/or Resin	4	5.4				L½	М	N	0	0½	Р	Q	R	R½		
Fairwaymaster Mini	all analyses	Poly-S	5	5.0				J½	К	L	L½	M½	N	N½				
H2PRO	H2PRO Granules	wetting agent	5	4.0		H1/2	I	J										

- · Recommended spreader settings are given for a walking speed of approximately 5km/hour.
- Given spreader settings are recommendations only. Exact rates, using the settings given in this table, cannot be guaranteed as rates are dependent on the spreader itself and the accuracy of the person operating it.
- · Calibrate the spreader at regular intervals.

